

Date _____

Customer code C- _____

Invoice address _____

Contact person _____

Your reference _____

Other delivery address _____

☐ Invoice address = delivery address☐ Quote

DECON E-DRIVE



Please add the order form for the standard chair and always request a complete quote.

Mounting on the Netti wheelchair is included – the standard wheels will remain with the manufacturer.

☒ = Standard equipment

Item no.		Description	
D70001	☒	Decon E-Drive with standard configuration as stated below	
D71016	☐	Mounting kit for Netti chairs (required)	
D70013*	☐	Delivery with standard Netti main wheels for wheel combination 24" + 7" incl. quick release and bushers (A constant change between Decon and Netti wheels is only possible as special adaptation)	
D800*	☐	Delivery with standard Netti main wheels for other wheel combinations than 24" + 7" incl. quick release, bushers and other necessary parts (a constant change between Decon and Netti wheels is only possible as special adaptation)	
Battery and charger			
Standard	☒	NiMH battery with a max range of approx. 18 km	
D70011	☐	Li-ion battery with a max range of approx. 32 km	
Standard	☒	Battery charger 100-240V	
D70021	☐	Power converter for car 12V	

NORWAY: Alu Rehab AS | Bedriftsvegen 23 | N-4353 Klepp stasjon | post.klepp@Meyragroup.com | Phone +47 51 78 62 20

DENMARK: Alu Rehab ApS | Kløftehøj 8 | DK-8680 Ry | info.ry@Meyragroup.com | Phone +45 87887300

All prices are list prices excl. VAT | Right for changes reserved | Valid until a new pricelist will be published | Page 1 of 4

Version: 2025-09

*Not available for the Netti AdaptPro and Netti Dynamic AdaptPro.

** These options are only available for Netti AdaptPro and Netti Dynamic AdaptPro as special adaptation.

User weight	
Standard	☒ Max user weight 125 kg
D70031	☐ Heavy duty version - max user weight 150 kg by 20", 22", 24" or 26" wheels Rims and spokes are made from a stronger material

Wheel size and accessories	
D71015*	☐ Anti-tippers (required - except if combined with a universal device holder)
D71000*	☐ 16" Flexel fine tread wheels (max. capacity 100 kg)
D71001*	☐ 20" fine tread pneumatic wheels with aluminium push rims
D71002*	☐ 22" fine tread pneumatic wheels with aluminium push rims
Standard	☒ 24" x 1 3/8 fine tread pneumatic wheels with aluminium push rims
D71003*	☐ 26" x 1" fine tread pneumatic wheels with aluminium push rims (only for the Netti III family)
D71004	☐ PU wheels x1 (available for 20", 22", 24" and 26" x 1")
D71014	☐ PU wheels wide x1 3/8 (available for 22" and 24" x 1 3/8")
D71005	☐ Spoke guards, transparent (available for 20"-26" wheels)



[A]



[B]

Driving unit	
Standard/ D71006	☒ Joystick for user, swing-away arm [A] ☒ Right ☐ Left
D71007R/ D71007L**	☐ Joystick mounted for use by caregiver ☒ Right ☐ Left
D71008R**	☐ Attendant control instead of joystick [B] ☒ Right
D71009R/ D71009L**	☐ Second joysticks for caregiver [2xA] ☒ Right ☐ Left
D71010R**	☐ Attendant control in addition to the joystick [A+B] ☒ Right



Mounting		
Standard	☒	Behind the back of the wheelchair, including bag for mounting
SPECIAL	☐	For chairs with dynamic back unit a special holder for the battery under the frame must be requested

Please note:

- Netti 4U chairs adjusted in seat depth 500 mm require frame extension.
- The mounting of wide front wheels (min. 45 mm) is required.
- For chairs with seat width extension, please contact customer service.
- When mounted on a chair from the Netti AdaptPro Family, a frame brake is not possible, therefore only the Decon E-Drive brake is available.

Specifications

Motor	Yamaha motors: 24V 120W
Battery types	NiMH battery, 24V x 6.7Ah - range 18 km Li-ion battery, 25V x 11.8Ah - range 32 km
Wheel	7 kg
Total weight	16 kg (including NiMH battery) 17.5 kg (including Li-ion battery)
Total chair width	E-Drive increases the total width with approx. 40 mm

Netti 4U Family: SW + app. 230 mm

Netti III Family with/without frame extension: SW + app. 256/245 mm

*Please note that frame extension is included in some options like Extra-long seat depth, dynamic back solutions etc. Please contact customer service for questions.

Netti III Family with 16" Decon E-Drive: SW + app. 260 mm

Netti AdaptPro Family (special adaptation): SW + app. 245 mm

Netti V Family (special adaptation): SW + app. 235 mm

Netti V Family with 16" Decon E-Drive (special adaptation): SW + app. 215 mm

**Please be aware that adjustments of Netti V can easily influence the total width – always request a specific quote with measurements.

Wheel dimensions	16", 20", 22", 24", 26"
Air pressure	6 Bar, 600 kPa
Speed	0-6 km/t
Maximum range with fully charged battery	Approx. 18 km with NiMH battery/ Approx. 32 km with Li-ion battery in accordance with ISO 7176-4
Fuse	30 A (flat)
Max user weight	Up to 125 kg (for 16": up to 100 kg)
Max user weight "Heavy-duty"	Up to 150 kg Rims and spokes are made from a stronger material
Max gradient	6°
CE mark	Complies with EU-Directive 93/42/EEC
Joystick	Contactless sensing by single-chip/ Std. fitted on right side swing-away arm.
Force alteration	By optional spring (for individual optimization)
USB charger	Auxiliary USB port (5V, 500 mA max.)
Display device	LCD (Vertical aligned)
Parameter setting	Onboard (joystick) / via PC (Smart Tune)
Battery charger	100 to 240V AC, 50/60Hz (standard) A power converter for car is available as accessory.
Rated power	37V. 26A (when charging)
Charging time	Normal charging time approx. 2-3 hours
Possible combinations	Please add the order form for the standard chair and always request a complete quote.