

Date _____

Customer code C- _____

Invoice address _____

Contact person _____

Your reference _____

Other delivery address _____

☐ Invoice address = delivery address☐ Quote☒ = Standard equipment

DECON E-MOVE



Please add order form for the standard chair.

Mounting on the Netti wheelchair is included – the standard wheels will remain with the manufacturer.

Item nr.	Description	
D70002	☒ Decon E-Move with standard configuration as stated below and Netti adaptors	
D71016	☐ Mounting kit for Netti chairs	
Battery and charger		
Standard	☒ NiMH battery with a max range of approx. 18 km	
D70012	☐ Li-ion battery with a max range of approx. 30 km	
Standard	☒ Battery charger	
D70022	☐ Power converter for car	
User weight		
Standard	☒ Max user weight 125 kg	
D70032	☐ Heavy duty version - max user weight 150 kg Rims and spokes are made from a stronger material	
Wheel size		
D72001	☐ 20" fine tread pneumatic wheels with stainless steel push rims	
D72002	☐ 22" fine tread pneumatic wheels with stainless steel push rims	
Standard	☒ 24" fine tread pneumatic wheels with stainless steel push rims	
D72003	☐ 26" fine tread pneumatic wheels with stainless steel push rims (only for Netti III family)	

Tyres	
Standard	☒ Fine tread pneumatic wheels
D72004	☐ PU wheels
Push rims and spoke guards	
Standard	☒ Stainless steel push rims
D72005	☐ Poly compact push rims
D72006	☐ Poly gel push rims
D72007	☐ Max grip push rims
D72008	☐ Transparent spoke guards
Programs	
D72009	☐ Second profile With this option, there is an extra button on the wheelchair. You can switch between two pre-programmed settings, which you can define yourself. For example, for inside and outside driving.
Flex handles	
Standard	☒ Power switch
D72010	☐ Power switch Flex handle to make it easier to reach the switch, 150 mm
D72011	☐ Power switch Flex handle to make it easier to reach the switch, 210 mm
D72013	☐ Second profile switch Flex handle to make it easier to reach the switch, 150 mm
D72014	☐ Second profile switch Flex handle to make it easier to reach the switch, 210 mm
Mounting of battery	
Standard	☒ Behind the back of the wheelchair, including bag for mounting
Netti wheels	
D70013	☐ Delivery with standard Netti main wheels for wheel combination 24"+7" incl. quick release and bushers (a constant change between Decon and Netti wheels is only possible as special adaptation)
D800	☐ Delivery with standard Netti main wheels for other wheel combinations than 24"+7" incl. quick release, bushers and other necessary parts (a constant change between Decon and Netti wheels is only possible as special adaptation)

Specifications

Motor	Yamaha motors: AC servomotor, 24V 110W
Battery types	NiMH, 24 V, 6.7 Ah, (160.8 Wh) range 18 km Li-ion, 25 V, 11.8 Ah (280 Wh) range 30 km
Wheel	7 kg
Total weight	17 kg (including NiMH battery) 18 kg (including Li-ion battery)
Total chair width	Netti 4U CED: Seat width approx. + 220 mm Netti III Family: Seat width approx. + 260 mm E-Move increases the total width with approx. 40 mm
Wheel dimensions	20", 22", 24" or 26"
Air pressure	6 Bar, 600 kPa
Speed	0–6 km/h
Maximum range with fully charged battery	Approx. 18 km with NiMH battery Approx. 30 km with Li-ion battery in accordance with ISO 7176-4
Fuse	30A (flat)
Max user weight	130 kg
Max user weight "Heavy-duty"	150 kg
Max gradient	6°
CE mark	Complies with EU-Directive 93/42/EEC
Battery charger	100 to 240V AC, 50/60H
Estimated effect	37V 26A (when charging)
Rated power charging time	Normal charging time approx. 2–3 hours NiMH & Li-ion. Service charge NiMH: 3-13 hours, full capacity (once every 13-26 charges)
Possible combinations	Please send us a request for a combination with other options of the selected wheelchair as some combinations might not be possible.